




- ▲ User-friendly
- ▲ Cost-saving
- ▲ Very complete as standard

Hoefnagels Fire Safety
Zevenheuvelenweg 50
5048 AN Tilburg
PO Box 5036
5004 EA Tilburg

Tel. +31 13 4625959
info@hoefnagels.com
www.hoefnagels.com



By Appointment
to the Court of
The Netherlands

Smartbox Firescreen Control

Control unit regulating how and when fire and smoke protection doors react to fire alarms or power failures. Applicable in combination with Firescreen fire-resistant roller screens and Smokescreen smoke-resistant roller screens.

Function

- ▲ Self-closing in the event of a power failure
- ▲ Emergency power battery in control unit
- ▲ Connection to fire alarm system
- ▲ Ready to connect smoke and temperature detectors
- ▲ Maintenance, voltage and fire alarms
- ▲ Simple to extend

Version

- ▲ Unit size: 320 x 240 x 130 mm (w x h x d)
- ▲ LED display size: 98 x 65 x 37 mm (w x h x d)
- ▲ 230V, 50Hz (also available in 24 Volt version)
- ▲ Power consumption 100W
- ▲ Power cord for standard wall socket
- ▲ Plastic housing with protection class: IP56

Options

- ▲ Smoke and temperature switches
- ▲ Acoustic signal generator
- ▲ Optical signal transmitter
- ▲ Possibility to connect 2 screens to 1 Firescreen Control

External LED display

The external LED display is used with Firescreen fire resistant roller blinds whose control system cannot or must not be mounted in sight. The display shows that the screen is connected to the mains and/or battery voltage and gives a message in case of fire or when maintenance is required.

