

Declaration of Performance

No. HB-DOP-0003

1. Unique product identification code:

Firescreen® Radiation EW30

2. Type number:

Radiation EW30

3. Intended use:

Fire and Smoke protecting curtain for

compartmentation

Max length of gap = 19200 mm = 2xHeight + Width High and low density rigid supporting construction

Standard Flexible supporting construction

4. Name and address of manufacturer:

Hoefnagels Fire Safety Holding bv

Zevenheuvelenweg 50

5048 AN Tilburg Nederland

5. Name and address of representative:

N/A

6. System of assessment and verification of

constancy of performance:

EN 16034:2014 - System 1

EN 13241:2003+A2:2016 - System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Notified product certification body EFECTIS France, No. 1812, performed the determination of the product type on the basis of type testing (including sampling), initial inspection of the manufacturing plant and of the factory production control and continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance of the product.





8. Declared performance:

| Essential characteristics | Performance | Harmonized technical Specification |
|---|------------------------|---------------------------------------|
| Resistance to fire (for fire | | |
| compartmentation uses): | | |
| E | 30 | |
| EI ₁ | NPD | |
| EI ₂ | NPD | |
| EW | 30 | |
| Smoke control | Sa | EN 16034:2014 |
| Ability to release | released | |
| Self-closing | С | |
| Durability of ability to release | release | |
| • | maintained | |
| Durability of self-closing: | | |
| - against degradation (cycling testing): | Cat. of use 0, 1 or 2* | |
| - against ageing (corrosion): | NPD | |
| Watertightness | NPD | |
| Release of dangerous substances | NPD | |
| Resistance to wind load | Class 0 | |
| Thermal resistance (where relevant) | NPD | EN 13241:2003+A2:2016 |
| Air permeability | NPD | |
| Safe opening (for vertically moving doors) | Pass | |
| Definition of geometry of glass components | NPD | |
| Mechanical resistance and stability | NPD | |
| Operating forces (for power operated doors) | NPD | |
| Durability of watertightness, thermal | NPD | |
| resistance and air permeability against | | |
| degradation | | |

^{*}depending on the dimensions of the curtain NPD = No performance determined

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

G.J.B. Hoefnagels, Director

Tilburg, 07-07-2025