



- ▲ User-friendly
- ▲ Cost-saving
- ▲ Very complete as standard

Hoefnagels Fire Safety

Zevenheuvelenweg 50
 5048 AN Tilburg
 PO Box 5036
 5004 EA Tilburg

Tel. +31 13 4625959
 info@hoefnagels.com
 www.hoefnagels.com

Smartbox Smart Control

Control unit that regulates how and when fire and smoke protection doors react to fire alarms or power failures. Applicable in combination with Firelock fire rated roller shutters, non-fire rated roller shutters and roll-up grilles.

Function

- ▲ Self-closing in the event of a power failure
- ▲ Emergency power battery in control unit
- ▲ Connection to fire alarm system
- ▲ Ready for connection of smoke and temperature detectors
- ▲ Maintenance, voltage and fire alarms
- ▲ Easily extendable
- ▲ Running time protection
- ▲ Motion counter
- ▲ Continuous current measurement
- ▲ Standard 1 second reverse polarity time
- ▲ Summer/winter mode

Version

- ▲ Unit size: 320 x 240 x 130 mm (w x h x d)
- ▲ 230V, 50Hz (also available in 24 Volt version)
- ▲ Power consumption 100W
- ▲ Power cord for standard wall socket
- ▲ Plastic housing with protection class: IP56

Opties

- ▲ Central control
- ▲ Under control protection
- ▲ Photocell protection
- ▲ Child protection
- ▲ Remote control
- ▲ Interlock function between 2 doors
- ▲ Smoke and temperature detectors
- ▲ Traffic control:
 - Red or green signal lights
 - Card readers
 - Loop detectors

External LED display

The external LED display is used for Firescreen fire resistant roller blinds where the control system cannot or must not be mounted in sight. The display shows that the screen is connected to the mains and/or battery voltage and gives a message in case of fire or when maintenance is required.



By Appointment
 to the Court of
 The Netherlands